



Colorbond® Fencing



For an installation guide
please go to
[http://www.lysaght.com/fencing/
fencing-installation-information](http://www.lysaght.com/fencing/fencing-installation-information)

THE FENCING FACTORY
TEL: 472 5 6003
29-31 Auscan Crescent
Garbutt Qld 4814
www.fencingfactory.com.au
✉: sales@fencingfactory.com.au

Colorbond® Fencing

A fence made of COLORBOND® steel is a secure, strong and beautiful addition to your home.

- ◆ Available in a choice of 14 standard designer colours and 10 secondary colours.
- ◆ Strong and durable.
- ◆ Easy to maintain.
- ◆ Won't rot, burn or be eaten by termites.
- ◆ Enhances the security of your home and family.

Colorbond® COLOUR RANGE

STANDARD FENCING COLOUR RANGE



SECONDARY FENCING COLOUR RANGE



EXTENDED FENCING COLOUR RANGE



Please check with your local supplier regarding specific colour availability for this product.

Panel Size: 2.35m wide

Neetascreen

2.1m	\$192.00
1.8m	\$171.00
1.5m	\$151.00
1.2m	\$130.00

Smartascreen

2.1m	\$192.00
1.8m	\$171.00
1.5m	\$151.00
1.2m	\$130.00

Miniscreen

2.1m	\$278.00
1.8m	\$254.00
1.5m	\$224.00
1.2m	\$196.00

Colorbond Gates

Fittings include: Frame, Infill Sheet, Rail, Post, Cap, Hinges and Key Lock

Neetascreen or Smartascreen Styles

Double Gate	1.8m	\$ 1,317.00
Suits a 3040mm opening	1.5m	\$ 1,193.00

Single Gate	1.8m	\$ 658.00
Suits a 960mm opening		

Posts: 65mm sq galvanised steel powder-coated corner, end and bracing to be installed every 2-3 panels	2.67m	\$ 77.55
---	-------	----------

All pricing is including GST. Valid from September 2021

Simple maintenance of COLORBOND® steel by regular washing with water, will not only enhance its life but maintain its attractiveness for longer periods. Areas not regularly washed by rainwater should be hosed down at least every six months and more frequently in coastal areas/high levels of industrial fallout occur.

In cases where the regular maintenance referred to above does not remove all dirt, the following procedure should be carried out:

- Wash the surface with a mild solution of pure soap or mild non-abrasive kitchen detergent in warm water with a soft sponge or soft cloth.
- The COLORBOND® should be thoroughly rinsed with clean water immediately after cleaning to remove traces of detergent.

If cared for in accordance with these instructions, your building components made from COLORBOND® pre-painted steel and ZINCALUME® steel will give many years of low maintenance life.

